



Product Range	EVO SLIM
Product Reference	EVOS 128 / 135 / 149 / 154 / 228 / 235 / 249 / 254
Description	Suspended direct/indirect luminaire, c/w low glare wedge louvre - prismatic panel available on request - colour finish silver or white as standard – other colours available on request. Infill Plates and Corners available.
Principle Application	Office Lighting
Lamp Type	TL-5 – 28w, 35w, 49w, 54w
Lamp Cap	G5
Control Gear	Philips HF-Performer (DALI, DSI and 1-10v dimmable versions available).
System Power	Min 33w, Max 118w
Weight	7 – 7.7kg
Technical Specification	Housing made from 0.8 Zintec. Supplied with 1.5m 3 core LSF lead and 3m adjustable wire rope suspension.
IP Rating	IP20
Supply Voltage	220-240V
Dimensions	128, 154, 228 & 254 - 1240mm x 180mm x 42mm. 135, 149, 235 & 249 - 1540mm x 180mm x 42mm
Mounting Arrangement	Suspended via adjustable wire ropes. Suspension of 250mm – 3000mm
Mains Connection Arrangement	Fused terminal block
Lighting characteristics	DLOR 33%, ULOR 49%, TOTAL 82%

High Technology Lighting Ltd has a policy of continual design and development. As a result specifications and dimensions are subject to change without notice.