

Luminaire Data Sheet



Product Range	SIGNATURE
Product Reference	DFPE 1232 (2 x 36W), DFPE 1532 (2 x 58W) DFPE 663 (3 x 18W), DFPE 664 (4 x 18W)
Description	Surface mounted TL-8 fluorescent housing with choice of WPE2 LG3 Cat 2 louvre, RPE polished ribbed cross blade louvre, or PPE TP(a) rated prismatic panel.
Principle Application	Office lighting.
Lamp Type	TL-8
Lamp Cap	G13
Control Gear	Philips HF-Performer (DALI, DSI and 1-10v versions available).
System Power	Min 54W Max 107W
Weight	11kg max.
Technical Specification	Housing manufactured from 0.7 zintec, powder coated white, with white profiled moulded end caps.
IP Rating	IP20
Supply Voltage	220-240V
Dimensions	1262mm x 362mm (2 x 36W), 1562mm x 362mm (2 x 58W) 662mm x 662mm (3 x 18W & 4 x 18W)
Mounting Arrangement	Surface mounted
Mains Connection Arrangement	Terminal block.
Lighting characteristics	DLOR 59%, ULOR NIL, TOTAL 59% (typical)

High Technology Lighting Ltd has a policy of continual design and development. As a result specifications and dimensions are subject to change without notice.