



Product Range	ACCOLADE
Product Reference	DFREC 663 (3 x 18w) / 664 (4 x 18w) / 1232 (2 x 36w) 1263 (3 x 36w) / 1264 (4 x 36w) / 1532 (2 x 58w)
Description	Recessed luminaire with a choice of WPE2, LG3 Cat 2 louvre, RPE polished ribbed cross blade louvre or PPE TP(a) rated prismatic panel.
Principle Application	Office Lighting
Lamp Type	TL-8
Lamp Cap	G13
Control Gear	Philips HF-Performer (DALI, DSI and 1-10v versions available).
System Power	Min 57w, max 140w
Weight	6kg max
Technical Specification	Housing fabricated from 0.7 zintec.
IP Rating	IP20
Supply Voltage	220-240V
Dimensions	Nominal 600mm x 600mm (3 & 4 x 18w), 1200 x 300mm (2 x 36w), 1200 x 600mm (3 & 4 x 36w), 1500 x 300mm (2 x 58w).
Mounting Arrangement	Recessed in to ceiling grid.
Mains Connection Arrangement	Fused terminal block
Lighting characteristics	DLOR 55%, ULOR Nil, Total 55% typical.

High Technology Lighting Ltd has a policy of continual design and development. As a result specifications and dimensions are subject to change without notice.