



Louvre and Controller Options

Louvre Ref


WPA2 : WNA2
TL Wishbone Sprung
WPE2 : WNE2
TL Lift & Tilt
WCA2
PLL Wishbone Sprung
WCE2
PLL Lift & Tilt



Wishbone Sprung and Lift & Tilt specular (polished) wedge LG3 CAT2 louvre range, encompassing TL and PLL compact fluorescent lamp types. Designed and independently tested to conform to the **CIBSE LG3 1996** best practice guidelines for lighting environments where a fairly wide spread usage of display screens (VDTs) is intended i.e. in office/data processing areas. Louvres achieve the required 200 cd/m or less at the limiting angle of 65 degrees. A semi-specular (matt) louvre finish can be supplied on request.

Louvre Ref


WPA3
TL Wishbone Sprung
WPE3
TL Lift & Tilt
WCA3
PLL Wishbone Sprung
WCE3
PLL Lift & Tilt



Wishbone Sprung and Lift & Tilt specular (polished) wedge LG3 CAT2 louvre range, encompassing TL and PLL compact fluorescent lamp types. Designed and independently tested to conform to the **CIBSE LG3 1996** best practice guidelines for lighting environments where a fairly wide spread usage of display screens (VDTs) is intended i.e. typical office areas. Louvres achieve the required 200 cd/m or less at the limiting angle of 75 degrees. A semi-specular (matt) louvre finish can be supplied on request.

Louvre Ref

WCPA : WCNA
TL Wishbone Sprung
WCPE : WCNE
TL Lift & Tilt
WCCA
PLL Wishbone Sprung
WCCE
PLL Lift & Tilt




Wishbone Sprung and Lift & Tilt polished louvre with a white cross blade for TL and PLL compact fluorescent lamp types.

The combination of a polished louvre with a white cross blade offers the lighting specifier a high lumen output, with a degree of eye catching brightness across the ceiling line. This range of louvres is ideal for retail environments that wish to promote an inviting, welcoming atmosphere with a degree of glare control.

Louvre Ref


RPA : RNA
TL Wishbone Sprung
RPE : RNE
TL Lift & Tilt
RCA
PLL Wishbone Sprung
RCE
PLL Lift & Tilt



Wishbone Sprung and Lift & Tilt polished louvre with a low glare ribbed cross blade for TL and PLL compact fluorescent lamp types. Typical usage includes general office and retail stores where a high luminance level is required without excessive glare. Semi-specular (matt) louvre finish can be supplied on request.

Louvre Ref

WWA : WWNA
TL Wishbone Sprung
WWE : WWNE
TL Lift & Tilt
WWCA
PLL Wishbone Sprung
WWCE
PLL Lift & Tilt



Wishbone Sprung and Lift & Tilt all white louvre for TL and PLL compact fluorescent lamp types.

The all white aluminium material of this louvre offers maximum light diffusion creating high general lighting output and brightness across the ceiling line. This louvre range is ideal for retail environments wishing to promote a bright, inviting atmosphere.

Controller Ref

PPA
TL & PLL Wishbone Sprung
PPE
TL & PLL Lift & Tilt
PPG
TL & PLL Screw Fix Gasketed



Framed Wishbone Sprung, Lift & Tilt and Gasketed screw fix prismatic panels for TL and PLL compact fluorescent lamp. Panels are supplied as standard in TP(a) rated PVC

High Technology Lighting Ltd has a policy of continual design and development. As a result specifications and dimensions are subject to change without notice.