

Luminaire Data Sheet



Product Reference	DL06 117 / 118 / 126 / 132 / 142 / 217 / 218 / 226 / 232 / 242
Description	Recessed compact fluorescent downlight. Dropped glass attachments including IP rated sealed glass available. (Download Dropped Glass data sheet for details)
Principle Application	Accent lighting.
Lamp Type	17W PL-R 18W and 26W PL-C 32W & 42W PL-T Available in single and twin lamp versions.
Lamp Cap	GR14q-1 (17W PL-R) G24d-2 (18W PL-C) G24d-3 (26W PL-C) GX24q-3 (32W PL-T) GX24q-4(42W PL-T)
Control Gear	Philips HF-Performer
System Power	Please consult our Technical Office.
Weight	2kg max
Technical Specification	Die cast bezel in White. Injection moulded UL94 VO flame retardant control gear and lampholder housings. Supplied with 2m LSF cable
IP Rating	IP20
Supply Voltage	220-240V
Dimensions	237mm bezel, 222mm cut out, 209mm high
Mounting Arrangement	Recessed
Mains Connection Arrangement	Fused terminal block.
Lighting characteristics	DLOR 76.8%, ULOR NIL, TOTAL 76.8%

High Technology Lighting Ltd has a policy of continual design and development. As a result specifications and dimensions are subject to change without notice.