



Anti-vandal attachment



IP44 & IP54 Dropped Glass

Product Range	GRAVITY
Product Reference	DL05
Description	Recessed downlight
Principle Application	Corridors, amenity lighting
Lamp Type	13W, 18W, and 26W PL-C in single and twin lamp versions. 32W PL-T and 42W PL-T in single lamp version
Lamp Cap	G24d-3 (PL-C), GX24q-3 (PL-T)
Control Gear	Philips HF-Performer
System Power	Single 13W = 14W, Single 18W = 18W, Single 26W = 26W, Single 32W = 35W. Single 42W = 46W Twin 13W = 28W, Twin 18W = 38W, Twin 26W = 54W.
Weight	2kg max.(Emergency version 3kg max.)
Technical Specification	Die cast bezel, injection moulded UL94 VO flame retardant control gear/lampholder housings. Available with a wide range of attachments and remote emergency gear. Bezel available in White, Chrome, Gold, or Brushed Aluminium finish. Can be supplied with bezel with sealed glass and torque lock screws, and anti vandal side arm brackets.
IP Rating	IP20 to IP65 (with appropriate attachment)
Supply Voltage	220-240V
Dimensions	Bezel 194mm, Cut out 176mm
Mounting Arrangement	Recessed
Mains Connection Arrangement	Fused terminal block, supplied with 2m LSF cable
Lighting characteristics	DLOR 76.8%, ULOR NIL, TOTAL 76.8%

High Technology Lighting Ltd has a policy of continual design and development. As a result specifications and dimensions are subject to change without notice.